

Trailer model:	H7	H9	H11	H15
Crane model:	HFS	HFS	HFL	M65
load capacity (kg):	7000	9000	11000	15000
width (mm):	1950	2030	2250	2450
total length (mm):	5500	6150	6300	8750
length of the loading area (mm):	4000	4200	4500	4800
type of frame:	central frame (160x160x8)	central frame (160x160x8)	chest frame (2x200x100x6)	chest frame (2x250x100x5)
no. of bunks / no. of stakes:	4 bunks / 8 stakes	4 bunks / 8 stakes	12 pockets / 12 stakes	12 pockets / 12 stakes
wheels:	11,5/80x15	400/60x15,5	500/50x17	550/45x22,5
maximum hydraulic range (m):	5,2	5,2	7,0	8,7
crane at maximum reach with grapple and rotator (kg):	550	550	550	400
oil demand for work (l):	30 l	30 l	30 l	60 l
slewing torque 360°:	double	double	double	double
rotator capacity (kg):	3000	3000	3000	4500
wood grapple:	0,22	0,22	0,22	0,26
support legs:	vertical cylinders hydraulic at the trailer	vertical cylinders hydraulic at the trailer	vertical cylinders hydraulic at the trailer	hydraulic cylinders at the trailer fold out sideways
drawbar steering control:	-	2 hydraulic cylinders	2 hydraulic cylinders	2 hydraulic cylinders

### additional options:

additional extension (m):	no	yes (+1,8)	in standard	yes (+0,5)
crane lighting (LED):	yes	yes	yes	yes
additional pair of stakes:	yes	yes	yes	yes
hydraulic brakes:	yes	yes	yes	yes
air brakes:	yes	yes	yes	yes
loading area length extension 1,2m:	no	no	yes	yes
hydraulic drive:	no	no	yes	yes
open/close grapple extension of the crane electrical steering	no	yes (only for 7m crane)	yes	yes

[www.hydrofast.pl](http://www.hydrofast.pl)